

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended): A discharge bulb, comprising:

an arc tube fixedly positioned and forwardly elongating from an insulating base positioned behind said arc tube, the arc tube comprising: a ceramic, straight, and cylindrical light emitting tube having sealed end portions to form an enclosed space therein; and electrodes opposingly disposed in said light emitting tube, wherein said enclosed space is filled with a light emitting substance and a starting rare gas; and

a strip-shaped first light blocking portion disposed at a first portion of said light emitting tube that corresponds to at least a rear one of the sealed end portions of said light emitting tube,

wherein said first light blocking portion extends, in a circumferential direction, over at least a range from an upper side to both lateral sides of said light emitting tube, said first light blocking portion being provided as a portion of said light emitting tube or being provided radially outside of said light emitting tube.

2. (previously presented): The discharge bulb according to claim 1, further comprising: a second light blocking portion disposed at a second portion of said light emitting tube that corresponds to a front one of the sealed end portions of said light emitting tube,

wherein said second light blocking portion extends, in the circumferential direction, over at least a range, from a lower side to both of said lateral sides of said light emitting tube.

3. (previously presented): The discharge bulb of claim 2, wherein said second light blocking portion has a width, in an axial direction of the light emitting tube, at least

AMENDMENT UNDER 37 C.F.R. § 1.114(c)  
U.S. Appl. No. 10/750,858

corresponding to a width, in the axial direction, of said front sealed end portion of said light emitting tube.

4. (previously presented): The discharge bulb of claim 1, wherein said first light blocking portion has a width, in an axial direction of the light emitting tube, at least corresponding to a width, in the axial direction, of said rear sealed end portion of said light emitting tube.

5. (previously presented): The discharge bulb of claim 1, wherein said first light blocking portion extends in the circumferential direction on both the lateral sides of said light emitting tube to positions that horizontally coincide in level with a lowermost position of said rear end sealed portion of said light emitting tube.

6. (previously presented): The discharge bulb of claim 2, wherein said second light blocking portion extends in the circumferential direction on both the lateral sides of said light emitting tube to positions that horizontally coincide in level with an uppermost position of said front end sealed portion of said light emitting tube.

7. (previously presented): The discharge bulb of claim 1, wherein said first light blocking portion is disposed in the circumferential direction over a whole circumference of said light emitting tube.

8. (previously presented): A discharge bulb, comprising:

AMENDMENT UNDER 37 C.F.R. § 1.114(c)  
U.S. Appln. No. 10/750,858

an arc tube fixedly positioned and forwardly elongating from an insulating base positioned behind said arc tube, the arc tube comprising: a ceramic, straight, and cylindrical light emitting tube having sealed end portions to form an enclosed space therein; and electrodes opposingly disposed in said light emitting tube, wherein said enclosed space is filled with a light emitting substance and a starting rare gas;

an ultraviolet-ray blocking glass shroud surrounding said light emitting tube; and

a strip-shaped first light blocking portion disposed at a first portion of said light emitting tube that corresponds to at least a rear one of the sealed end portions of said light emitting tube,

wherein said first light blocking portion extends, in a circumferential direction, over at least a range from an upper side to both lateral sides of said light emitting tube.

9. (previously presented): The discharge bulb according to claim 8, further comprising: a second light blocking portion disposed at a second portion of said light emitting tube that corresponds to a front one of said sealed end portions of said light emitting tube,

wherein said second light blocking portion extends, in the circumferential direction, over at least a range from a lower side to both of said lateral sides of said light emitting tube.

10. (previously presented): The discharge bulb of claim 9, wherein said second light blocking portion has a width, in an axial direction of the light emitting tube, at least corresponding to a width, in the axial direction, of said front sealed end portion of said light emitting tube.

AMENDMENT UNDER 37 C.F.R. § 1.114(c)  
U.S. Appln. No. 10/750,858

11. (previously presented): The discharge bulb of claim 8, wherein said first light blocking portion has a width, in an axial direction of the light emitting tube, at least corresponding to a width, in the axial direction, of said rear sealed end portion of said light emitting tube.

12. (previously presented): The discharge bulb of claim 8, wherein said first light blocking portion extends in the circumferential direction on both the lateral sides of said light emitting tube to positions that horizontally coincide in level with a lowermost position of said rear end sealed portion of said light emitting tube.

13. (previously presented): The discharge bulb of claim 9, wherein said second light blocking portion extends in the circumferential direction on both the lateral sides of said light emitting tube to positions that horizontally coincide in level with a an uppermost position of said front end sealed portion of said light emitting tube.

14. (previously presented): The discharge bulb of claim 8, wherein said first light blocking portion is disposed in the circumferential direction over a whole circumference of said light emitting tube.

15. (currently amended): A discharge bulb, comprising:  
an arc tube fixedly positioned and forwardly elongating from an insulating base positioned behind said arc tube, the arc tube comprising: a ceramic, straight, and cylindrical light

AMENDMENT UNDER 37 C.F.R. § 1.114(c)  
U.S. Appln. No. 10/750,858

emitting tube having sealed end portions to form an enclosed space therein; electrodes opposingly disposed in said light emitting tube, wherein said enclosed space is filled with a light emitting substance and a starting rare gas; and

means for positioning a hot zone of a luminous distribution at a cutoff line of said luminous distribution, and substantially reducing a glare light output, said means for positioning the hot zone being provided as a portion of said light emitting tube or being provided radially outside of said light emitting tube.

16. (previously presented): The discharge bulb of claim 15, wherein:

said means for positioning and substantially reducing comprises a strip-shaped first light blocking portion disposed at a first portion of said light emitting tube that corresponds to at least a rear one of the sealed end portions of said light emitting tube; and

said first light blocking portion extends, in a circumferential direction, over at least a range from an upper side to both lateral sides of said light emitting tube.

17. (previously presented): The discharge bulb according to claim 16, wherein:

said means for positioning and substantially reducing further comprises a second light blocking portion disposed on a second portion of said light emitting tube that corresponds to a front one of the sealed end portions of said light emitting tube; and

said light blocking portion extends, in a circumferential direction, over at least a range from a lower side to both of said lateral sides of said light emitting tube.

AMENDMENT UNDER 37 C.F.R. § 1.114(c)  
U.S. Appl. No. 10/750,858

18. (currently amended) The discharge bulb of claim 17, wherein:

said second light blocking portion has a width, in an axial direction of the light emitting tube, at least corresponding to a width, in the axial direction, of said front sealed end portion of said light emitting tube; and

said first light blocking portion has a width, in the axial direction, at least corresponding to a width, in the axial direction, of said rear sealed end portion of said light emitting tube.

19. (currently amended) The discharge bulb of claim 16, wherein:

said first light blocking portion extends in the circumferential direction on both the lateral sides of said light emitting tube to positions that horizontally coincide in level with a lowermost position of said rear end sealed portion of said light emitting tube;

said second light blocking portion extends in the circumferential direction on both the lateral sides of said light emitting tube to positions that horizontally coincide in level with a an uppermost position of said front end sealed portion of said light emitting tube;; and

said first light blocking portion is disposed in the circumferential direction over a whole circumference of said light emitting tube.

20. (previously presented): The discharge bulb of claim 16, further comprising an ultraviolet-ray blocking glass shroud surrounding said light emitting tube.